



GRAIN MILLERS

Triticale

Official Purchasing Specification

Grading Factors

Quality Standards

	Spec	Min/Max
Test Weight	56	50
Moisture	13%	13.5%
Plump	70%	60%
Thins	0%	5%

Foreign Material

	Spec	Min/Max
FM	1.5%	3%
Total Other Grains	0%	2%
Ergot	0%	.04%

Damage

	Spec	Min/Max
Total Damage	0%	4%
Vomitoxin	0 ppm	1 ppm
Heated	0%	.2%
Falling #	170	150

FM (foreign material):

- All FM is deducted as dockage

Test Weight Conversions

<i>Lb/W.bu</i>	<i>g/0.5 L</i>	<i>Lb/W.bu</i>	<i>g/0.5 L</i>
49	316	54	300
49.5	319	54.5	303
50	322	55	306
50.4	325	55.5	309
50.9	328	56	312
51.5	332	56.5	315
52	335	57	318
52.5	338	57.5	321
52.9	341	58	324
53.5	297	58.5	327

Discounts MAY apply to any grain delivered out of spec.

* See Discount Schedule (reverse side)

- » FM –Thru 8/64” triangle sieve
- » Plump – On top of 6/64” slotted sieve
- » Moisture Tested on Dickey John

Pest/Pesticide/Odors - Restriction

- Triticale must NOT contain signs of infestations (dead or alive) or insect damaged kernels delivered to ANY GMI facility
- Triticale which has been treated with **glyphosate** as a pre-harvest desiccant will not be accepted
- Triticale must not contain detectable levels of pesticide, chemicals, or any objectionable odors

Contact Person

Conventional:

Mark Strabley

952-983-1309

mark.strabley@grainmillers.com