

GRAIN MILLERS TRITICALE

OFFICIAL PURCHASING SPECIFICATION

QUALITY STANDARDS

	Spec	Min/Max
Test	56 50	
Weight		
Moisture	13%	13.5%
Plump	70%	60%
Thins	0%	5%

FOREIGN MATERIAL

	Spec	Min/Max	
FM	0%	3%	
TOTAL OTHER	0%	2%	
GRAINS			
ERGOT	0%	.04%	

DAMAGE

	Spec	Min/Max	
TOTAL	0%	4%	
DAMAGE			
VOMITOXIN	0 ppm	1 ppm	
HEATED	0%	0.2%	
FALLING #	170	150	

TEST WEIGHT CONVERSIONS

Lb/W.bu	g/0.5 L	Lb/W.bu	g/0.5 L
49	316	54	348
49.5	319	54.5	351
50	322	55	354
50.4	325	55.5	357
50.9	328	56	361
51.5	332	56.5	364
52	335	57	367
52.5	338	57.5	370
52.9	341	58	374
53.5	345	58.5	377

Discounts may apply to any grain delivered out of spec.

- » FM –Thru 8/64" triangle sieve
- » Plump On top of 6/64" slotted sieve
- » Moisture Tested on Dickey John

PEST/PESTICIDE/ODOR RESTRICTIONS

- Triticale must **NOT** contain signs of infestation (dead or alive) or insect damaged kernels
- Triticale which has been treated with glyphosate as a pre-harvest desiccant will not be accepted
- Triticale must not contain detectable levels of pesticide, chemicals, or any objectionable odors

CONTACTS

Dan Patton 952-983-1278

dan.patton@grainmillers.com

CONVENTIONAL TRITICALE DISCOUNT SCHEDULE (Based on W.Bu, US\$)

Foreign Material (FM)

• All FM is deducted as dockage